

AIR LIFT UNIVERSAL STRUT SPEC SHEET

| Part # | Shock/Strut | Lower Mount | Replacement Air Spring | Airspring Diameter | Max Diameter @ 100PSI | Load Capacity @ 100PSI | Port Size | Maximum Mounting Height | Minimum Mounting Height | Stroke | Leader Hose |
|--------|-------------|--------------------------|------------------------|--------------------|-----------------------|------------------------|-----------|-------------------------|-------------------------|--------|-------------|
| 75559 | Strut | Spindle Tab Adapter Tube | 58523 | 6 | 7 | 2000lbs | 1/4 FNPT | 22.6 | 78.2 | 5.9 | Braided |
| 75561 | Strut | Spindle Tab Adapter Tube | 58523 | 6 | 7 | 2000lbs | 1/4 FNPT | 23.9 | 19 | 5.9 | Braided |
| 75562 | Strut | Spindle Tab Adapter Tube | 58523 | 6 | 7 | 2000lbs | 1/4 FNPT | 20.9 | 16 | 4.4 | Braided |
| 75563 | Strut | Spindle Tab Adapter Tube | 58462 | 4 | 4.6 | 750lbs | 1/4 FNPT | 23.9 | 19 | 5.9 | None |
| 75564 | Strut | Spindle Tab Adapter Tube | 58424 | 4 | 4.6 | 750lbs | 1/4 FNPT | 20.9 | 16 | 4.4 | None |
| 75566 | Shock | Clevis/Bushing | 58474 | 4 | 4.6 | 750lbs | 1/8 FNPT | 25.9 | 17.5 | 5 | None |
| 75567 | Strut | Spindle Tab Adapter Tube | 58415 | 5 | 5.6 | 1000lbs | 1/4 FNPT | 23.9 | 19 | 5.9 | None |
| 75568 | Strut | Spindle Tab Adapter Tube | 58315 | 5 | 5.6 | 1000lbs | 1/4 FNPT | 20.9 | 16 | 4.4 | None |
| 75569 | Shock | Clevis/Bushing | 58325 | 5 | 5.6 | 1000lbs | 1/8 FNPT | 25.9 | 17.5 | 5 | None |
| 75592 | Shock | Clevis | NONE | 5 | 5.6 | 750lbs | 1/4 FNPT | 23 | 11.8 | 5.1 | None |